

# SUPER TREASURY HIGH SECURITY SAFE UL TRTL 30X6

Our customers say:  
"This is definitely the best safe in the world"

For protection of: Cash, diamonds,  
jewelry, valuable documents, etc.



color RAL 7040



color RAL 7039





I.S.M. SAFES AND CASTING LTD.

# SUPER TREASURY HIGH SECURITY SAFE UL TRTL 30X6

## FEATURES

- ISM Super Treasury designed to combat the spectrum of modern criminal attacks.
- ISM Super Treasury tested by UL and certified according to UL TRTL30X6.
- Special barrier materials protect against a variety of burglary attack types.
- Sophisticated independent relocers.
- Four ways engagement boltwork.
- A wide variety of mechanical and electronic locks.
- Pre equipped for connection to an alarm system.
- Adjustment shelves and others options in order to meet customer requirements.
- There are a wide variety of colors to choose from.

## DOOR and BODY

- The overall thickness of the door is 196 mm (7.72") constructed of a 82 mm (3.22") thick layer of sophisticated barrier material to protect against burglary.
- The body casts in one piece for extra strength and protection.

## LOCKS

- ISM Super Treasury comes equipped as standard with U.L listed group I combination lock and security key which includes double bits. There is a wide variety of mechanical and electronic combination locks which are optionally available.
- Preparation for connection to an alarm system.
- Preparation for three movement time locks – is optionally available.

## BOLTWORK & LOCKING MECHANISM


- The boltwork and locking mechanisms are strong constructions to withstand sophisticated methods of burglary.
- The bolts are 40 mm (1.57") diameter and slide out in three directions with fixed bolts on the hinge side of the door.

## RELOCKING DEVICES

- The area of the locks and the vital mechanism areas are protected from attack by a special glass plate which if tampered with, will release independent relocers of the locks. The locks are also protected by a sophisticated system that is being activated in a special way.

## INTERIOR FITTING

- Adjustable/removable shelves are available for setting up the safe interior to accommodate jewelry trays cash and other valuables.



MODEL	Interior dimension (in)			Exterior dimension (in)			Interior (Ft <sup>2</sup> )	Shelves	Weight (Lbs)	Door swing (in)		
	H	W	D	H	W	D*				A	B	C
ST 271916	27	19	16	37.4	29	28.5**	4.7	2	2,347	19	19	51
ST 272617	27	26	17	37.4	35.6	29.5**	6.9	2	2,750	26	62	64
ST 332023	33	20	20	42.4	30	35.5**	7.6	3	3,115	20	62	52.6
ST 332617	33	26	17	42.4	35.6	29.5**	8.4	3	3,016	26	62	64
ST 342417	34	24	17	43.4	33.6	29.5**	8.0	3	2,926	24	59.4	60
ST 442023	44	20	23	53.4	30	35.5**	11.7	4	3,951	20	62	52.6
ST 442617	44	26	17	53.4	35.6	29.5**	11.3	4	3,949	26	62	64
ST 472418	47	24	18	56.4	33.6	30.5**	11.7	4	4,180	24	60.4	60
ST 552023	55	20	23	64.4	30	35.5**	14.6	5	4,576	20	62	52.6
ST 552617	55	26	17	64.4	35.6	29.5**	14.1	5	4,574	26	62	64
ST 642023	64	20	23	73.4	30	35.5**	17.0	6	5,084	20	62	52.6
ST 642418	64	24	18	73.4	33.6	30.5**	16.0	6	4,983	24	60.4	60
ST 642617	64	26	17	73.4	35.6	29.5**	16.4	6	5,082	26	62	64
ST 643118	64	31	18	73.4	40.6	30.5***	20.7	6	6,080	31	59	76
ST 682617	68	26	17	73.4	35.6	29.5***	17.4	6	5,311	26	62	64
ST 683119	68	31	19	77	40.5	31.5***	23.2	6	5,980	31	70	76
ST 683626	68	36	26	77	45.5	38.5***	36.8	6	7,300	26	81	85.6

\*Add 3.55" to outside depth for handle (all models).  
 \*\* Add 2" to outside depth for hinges  
 \*\*\* Add 2.56" to outside depth for hinges  
 ■ Lock comes equipped as standard with U.L listed group I combination lock and security key which includes double bits. There is a wide variety of mechanical and electronic combination locks which are optionally available.  
 ■ Two colors to choose as standard: RAL 7039, 7040

■ Left swing - no charge  
 ■ Preparation (only) for movement time lock - no charge (according to request)  
 ■ Additional shelf-according to request  
 ■ Weight tolerance ±5%

## I.S.M Safes and casting LTD

phone: +97239068839 ■ fax: +97239068894  
 E-mail:ism@ism-safes.co.il ■ Website:www.ism-safes.co.il



PRINT COIL